

20W形

品番	消費電力(W)	全光束(lm)	色温度(K)	定格寿命(h)	口金	給電方式	管長(mm)	管径(mm)	製品図面
V-PHL20SSN/9.5-13	9.5	1,300	5,000	40,000	G13	片側	580	Φ28	
PHL20SSL/8-10	8	1,000	3,000	40,000	G13	片側	580	Φ28	
PHL20SSW/8-11	8	1,100	4,000	40,000	G13	片側	580	Φ28	
PHL20SSN/8-12	8	1,200	5,000	40,000	G13	片側	580	Φ28	
PHL20SSN/8-11/C	8	1,100	5,000	40,000	G13	片側	580	Φ28	
PHL20SSD/8-10	8	1,000	6,500	40,000	G13	片側	580	Φ28	

平均演色係数(Ra) 80以上(83)

 廃番商品

40W形

品番	消費電力(W)	全光束(lm)	色温度(K)	定格寿命(h)	口金	給電方式	管長(mm)	管径(mm)	製品図面
V-PHL40SSL/19-25	19	2,500	3,000	40,000	G13	片側	1,198	Φ28	
V-PHL40SSN/13-20	13	2,000	5,000	40,000	G13	片側	1,198	Φ28	
V-PHL40SSN/13-20WP	13	2,000	5,000	40,000	G13	片側	1,198	Φ28	
V-PHL40SSN/19-28	19	2,800	5,000	40,000	G13	片側	1,198	Φ28	
V-PHL40SSD/13-20	13	2,000	6,500	40,000	G13	片側	1,198	Φ28	
V-PHL40SSD/19-28	19	2,800	6,500	40,000	G13	片側	1,198	Φ28	
E-PHL40SSN/16.5-25.4	16.6	2,538	5,000	40,000	G13	片側	1,198	Φ26	
PHL40SSL/12-17	12	1,700	3,000	40,000	G13	片側	1,198	Φ28	
PHL40SSW/13-20	13	2,000	4,000	40,000	G13	片側	1,198	Φ28	
PHL40SSN/11-20	11	2,000	5,000	40,000	G13	片側	1,198	Φ28	
PHL40SSN/16-20	16	2,000	5,000	40,000	G13	片側	1,198	Φ28	
PHL40SSN/18-26	18	2,600	5,000	40,000	G13	片側	1,198	Φ28	
PHL40SSN/13-20/C	13	2,000	5,000	40,000	G13	片側	1,198	Φ28	
PHL40SSN/17-20/C	17	2,000	5,000	40,000	G13	片側	1,198	Φ28	
PHL40SSD/12-20	12	2,000	6,500	40,000	G13	片側	1,198	Φ28	
PHL40SSD/17-20	17	2,000	6,500	40,000	G13	片側	1,198	Φ28	

平均演色係数(Ra) 80以上(83)

110W形

品番	消費電力(W)	全光束(lm)	色温度(K)	定格寿命(h)	口金	給電方式	管長(mm)	管径(mm)	製品図面
PHL11SN/22-40	22	4,000	5,000	40,000	G13	片側	2,367	Φ33	
PHL11SN/32-40	32	4,000	5,000	40,000	G13	片側	2,367	Φ33	
PHL11SN/28-46	28	4,600	5,000	40,000	G13	片側	2,367	Φ33	
PHL11SD/28-44	28	4,400	6,500	40,000	G13	片側	2,367	Φ33	

平均演色係数(Ra) 80以上(83)